

Product Model. : IF2.6

Item.	Specifications
VERSION	IF2.6-XW08AN540000
Pixel Pitch	2.604 mm
LED Type	SMD3 in 1 (AOTO 1515)
Pixel Density	147,456 dots/m ²
Pixel Configuration	1R 1G 1B
Module Resolution	96 (W) x 96 (H) =9,216 dots
Module Size	Width: 250 mm; Height: 250 mm
Cabinet Resolution	192 (W) x 192 (H) =36,864 dots
Cabinet Size	Width: 500 mm, Height: 500 mm
Cabinet Area	0.25 m ²
Cabinet Weight	15±0.5 kg
Cabinet Material and Color	Die-casting Aluminum, Black
Uncalibrated Brightness	800nits
Viewing Angle	Horizontal: 140°±10°; Vertical: 140°±10°
Color Processing Depth	13 bit
Refresh Rate	3840 Hz
Contrast Ratio	3000:1
Input Voltage	AC100V to AC240V, 50 or 60 Hz
Maximum Power	180 W/cabinet; 720 W/m ²
Average Power	60 W/cabinet; 240 W/m ²
IP Rating	IP54
Maintenance	Front
Lifespan	100,000 hours
Operating Environment	Temperature: -20°C—50°C/ Humidity: 10% - 90%

*This parameter comes from laboratory test data, but it may be slightly different due to individual product differences, software versions, use conditions and environmental factors.

Please refer to the actual use.